



Model: ASYH30KMTB / ASYH36KMTB



Wireless RC



## Specifications

Model name	Indoor unit		ASYH30KMTB	ASYH36KMTB
	Outdoor unit		AOYH30KMTB	AOYH36KMTB
Power Source	Single phase, ~230V, 50Hz			
Capacity	Cooling	kW	8.0 (2.9~9.0)	9.4 (2.9~10.0)
	Heating		8.8 (2.2~11.8)	10.1 (2.7~12.6)
Input Power	Cooling/Heating	kW	2.33/2.20	3.16/2.73
	Cooling		3.43	2.97
EER	Cooling	W/W	4.00	3.70
	Heating		4.00	3.70
Pdesign	Cooling/Heating (+10°C)	kW	8.0/6.5	9.4/7.1
	Cooling		6.68	6.10
SEER	Cooling	W/W	4.50	4.50
	Heating (Average)		4.50	4.50
Energy Efficiency Class	Cooling	A	A++	A++
	Heating (Average)		A+	A+
Max. Operating Current	Cooling/Heating	A	21.0/21.0	21.5/21.5
	Cooling		419	534
Annual Energy Consumption	Cooling	kWh/a	1.994	2.189
	Heating		2.6	3.8
Moisture Removal	Cooling	l/h	50/44/40/33	50/44/40/33
	Heating		49/44/39/33	49/44/39/33
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	53/55	55/65
	Indoor (Heating)	H/M/L/Q	65/65	65/65
	Outdoor (Cooling/Heating)	High	68/69	70/70
	Indoor (Cooling/Heating)	High	1,330/3,750	1,330/3,750
Sound Power Level	Indoor (Cooling/Heating)	High	1,330/3,750	1,330/3,750
	Indoor/Outdoor (Cooling)	High	340 × 1,150 × 280	340 × 1,150 × 280
	Indoor/Outdoor (Heating)	High	788 × 940 × 320	788 × 940 × 320
	Indoor	mm	18.5(41)	18.5(41)
Net Dimensions H × W × D	Indoor	mm	52.0(115)	52.0(115)
	Outdoor	mm	9.52(15.88)	9.52(15.88)
Weight	Indoor	kg (lbs)	13.8(15.8 to 16.7)	13.8(15.8 to 16.7)
	Outdoor	kg (lbs)	50(30)	50(30)
Connection Pipe Diameter (Liquid/Gas)			30	30
Drain Hose Diameter (I.D./O.D.)			-15to+46	-15to+46
Max. Pipe Length (Pre-Charge)			-15to+24	-15to+24
Max. Height Difference			R32(675)	R32(675)
Operating Range	Cooling	°CDB	1.90(1.283)	1.90(1.283)
	Heating			
Refrigerant	Type (Global Warming Potential)			
	Charge	kg (CO <sub>2</sub> eq-T)		

## Optional parts

\* For optional parts compatibility of Intesis devices, refer to the optional parts compatibility list Page C-048.

Compact wired remote controller:	UTY-RCRY21	External connect kit:	UTY-KWZXZ5	Network Converter for single split (DC power supply type):	UTY-VTGV
Wired remote controller (touch panel):	UTY-RNRYZ5	External input and output PCB <sup>1)</sup> :	UTY-KCSXZ2	Network Converter for single split (AC power supply type):	UTY-VTGVX
Wired remote controller:	UTY-RLRY	WLAN adapter:	UTY-TFSXF2	Silver Ion Filter:	UTR-FA13-3
Simple remote controller (without operation mode):	UTY-RHRY		UTY-TFSXH3	External switch controller:	UTY-TERX
Simple remote controller:	UTY-RSRY		FG-AC-WIF1Z1	Communication kit:	UTY-TWRXZ2

\*1 It is required when 2 or more external input and output ports are used.

## Dimensions

(Unit: mm)

