





PRODUCT INFORMATION (*1)				
ROOM AIR CONDITIONER	INDOOR MODEL	MFZ-KW25VG		
	OUTDOOR MODEL	MUZ-KW25VGHZ		
Function (indicate if present)		If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season		
cooling		Y		
heating		Y		
		Average (mandatory)	Y	
		Warmer (if designated)	Y	
		Colder (if designated)	Y	
Item	symbol	value	unit	
<b>Design load</b>				
cooling	Pdesignc	2.5	kW	
heating/Average	Pdesignh	3.5	kW	
heating/Warmer	Pdesignh	1.9	kW	
heating/Colder	Pdesignh	5.1	kW	
<b>Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj</b>				
Tj=35°C	Pdc	2.5	kW	
Tj=30°C	Pdc	2.0	kW	
Tj=25°C	Pdc	1.2	kW	
Tj=20°C	Pdc	1.0	kW	
<b>Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj</b>				
Tj=-7°C	Pdh	3.3	kW	
Tj=2°C	Pdh	1.9	kW	
Tj=7°C	Pdh	1.3	kW	
Tj=12°C	Pdh	0.7	kW	
Tj=bivalent temperature	Pdh	3.5	kW	
Tj=operating limit	Pdh	2.6	kW	
<b>Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj</b>				
Tj=2°C	Pdh	1.9	kW	
Tj=7°C	Pdh	1.3	kW	
Tj=12°C	Pdh	0.7	kW	
Tj=bivalent temperature	Pdh	1.9	kW	
Tj=operating limit	Pdh	2.6	kW	
<b>Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj</b>				
Tj=-7°C	Pdh	3.3	kW	
Tj=2°C	Pdh	1.9	kW	
Tj=7°C	Pdh	1.3	kW	
Tj=12°C	Pdh	0.7	kW	
Tj=bivalent temperature	Pdh	3.5	kW	
Tj=operating limit	Pdh	2.6	kW	
Tj=-15°C	Pdh	2.6	kW	
<b>Bivalent temperature</b>				
heating/Average	Tbiv	-10	°C	
heating/Warmer	Tbiv	2	°C	
heating/Colder	Tbiv	-10	°C	
<b>Cycling interval capacity</b>				
for cooling	Pcycc	x	kW	
for heating	Pcyh	x	kW	
Degradation co-efficient	Cdc	0.25	-	
<b>Electric power input in power modes other than 'active mode'</b>				
off mode	P <sub>OFF</sub>	2.0	W	
standby mode	P <sub>SB</sub>	2.0	W	
thermostat - off mode	P <sub>TO</sub>	8.0	W	
crankcase heater mode	P <sub>CK</sub>	0.0	W	
<b>Capacity control (indicate one of three options)</b>				
fixed		N		
staged		N		
variable		Y		
<b>Annual electricity consumption</b>				
cooling	Q <sub>CE</sub>	103	kWh/a	
heating/Average	Q <sub>HE</sub>	1188	kWh/a	
heating/Warmer	Q <sub>HE</sub>	490	kWh/a	
heating/Colder	Q <sub>HE</sub>	3430	kWh/a	
<b>Other items</b>				
Sound power level (indoor/outdoor)	L <sub>WA</sub>	49/61	dB(A)	
Global warming potential	GWP (*2)	675	kgCO <sub>2</sub> eq.	
Rated air flow (indoor/outdoor)	-	492/1962	m <sup>3</sup> /h	
Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@MitsubishiElectric.co.jp			

(\*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.

(\*2) This GWP value is based on Regulation(EU)No.517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No. 626/2001, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.

**TECHNICAL DOCUMENTATION (1)**

ROOM AIR CONDITIONER	INDOOR MODEL	MFZ-KW25VG	600H*750W*215D (mm)
	OUTDOOR MODEL	MUFZ-KW25VGHZ	550H*800W*285D (mm)

Function	
cooling	Y
heating	Y


The heating season	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	Y

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
<b>Seasonal efficiency (2)</b>			
cooling	SEER	8.5	-
heating/Average	SCOP/A	4.1	-
heating/Warmer	SCOP/W	5.4	-
heating/Colder	SCOP/C	3.1	-

Energy efficiency class			
cooling	SEER	A+++	-
heating/Average	SCOP/A	A+	-
heating/Warmer	SCOP/W	A+++	-
heating/Colder	SCOP/C	B	-

Other items			
Sound power level (indoor/outdoor)	L <sub>WA</sub>	49/61	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP (3)	675	kgCO <sub>2</sub> eq.

identification and signature of the person empowered to bind the supplier	
	Tadashi Saito Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS(THAILAND) CO.,LTD

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No626/2011.  
(2) SEER/SCOP values are measured based on EN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.  
(3) This GWP value is based on Regulation(EU)No.517/2014 from IPCC 4th Assessment Report.  
For Regulation (EU) No. 626/2001, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.