

Indoor unit model name FDF100VH Outdoor unit model name FDC100VSA-W

Refrigerant	R32	GWP	6	75	
Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.					
Cooling mode					
SEER		5.8			
Energy efficie		A+			
Design load (I Energy consu		10.0		nor voor hoso	d on standard test results
					d on standard test results. used and where it is located.
Heating mode (A	verage)				
SCOP		4.0			
Energy efficie		A+			
Design load (I			kW	\ - <i>i</i>	
Declared capa		8.50		(-10°C)	
Back up heati			kW	(-10°C)	
Energy consu					d on standard test results.
Actual energ	gy consumption will	aepena on	now tr	ne appliance is	used and where it is located.
	Varmer) Optional				
SCOP		-			
Energy efficie		-		(2)-)	
Design load (I			kW	(2°C)	
Declared capa			kW	(2°C)	
Back up heati			kW	(2°C)	d on standard tost results
Energy consumption, - kWh per year.based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.					
	55 5 5 1 1 1				
Heating mode (C	older) Optional				
SCOP		-			
Energy efficie		-			
Design load (kW	(-22°C)	
Declared capa			kW	(-22°C)	
Back up heati	8 . ,		kW	(-22°C)	
Energy consu					d on standard test results.
Actual energy consumption will depend on how the appliance is used and where it is located.					
Sound power	level (indoor)	65		dB(A)	
	level (outdoor)	69		dB(A)	
1	-				