

Capacity	Cooling / Heating	2,7 (0,8–3,8) / 3,0 (0,9–4,3)	kW
Power Supply	Into Outdoor Unit	220 - 240 / 1 / 50	V / Ph / Hz
Power Input	Cooling / Heating	0,67 / 0,68	kW
Rated Power Input	Cooling / Heating		1,4 kW
Power Current	Cooling / Heating	3,1 / 3,2	A
Rated Power Current	Cooling / Heating		6,2 A
Pdesign	Cooling / Heating	2,7 / 2,7	kW
SEER / SCOP	-	8,5 / 4,6	W / W
Air Flow	Indoor Unit	610 / 570 / 540 / 470 / 440 / 420 / 390	m3 / h
Air Flow	Outdoor Unit	1950	m3 / h
Sound Pressure Level at 1 m	Indoor Unit	38 / 37 / 34 / 31 / 26 / 23 / 22 / 19	dB(A)
Sound Pressure Level at 1 m	Outdoor Unit		50 dB(A)
Sound Power Level	Indoor unit	58 / 51 / 48 / 45 / 40 / 37 / 36	dB(A)
Sound Power Level	Outdoor unit		61 dB(A)
Dehumidifying Volume	-		0,8 l / h
Refrigerant / Charge / Eq. CO2	-	R32 / 0,53 / 0,36	type / kg / t
Additional Refrigerant	-		16 g / m
Refrigerant Liquid Pipe	Diameter		01.04.2006 inch / mm
Refrigerant Gas Pipe	Diameter	3/8 / 9,5	inch / mm
Max pipe length without additional refrigerant	-		5 m
Min. / Max. Pipe Length	-		Mrz 15 m
Max. Elevation	-		10 m
Dimension (w x h x d)	Indoor Unit	837 × 293 × 200	mm
Dimension (w x h x d)	Outdoor Unit	732 × 555 × 330	mm
Package (w x h x d)	Indoor Unit	896 × 373 × 272	mm
Package (w x h x d)	Outdoor Unit	794 x 376 x 615	mm
Net / Gross Weight	Indoor Unit	9,5 / 11,5	kg
Net / Gross Weight	Outdoor Unit	25,0 / 27,5	kg
Set Temperature range	-	16 ~ 30	°C
Operating Temperature Range	Cooling	-15 ~ 50	°C
Operating Temperature Range	Heating	- 25 ~ 30	°C