

Capacity	Cooling / Heating	3,5 (0,9–4,4) / 3,8 (0,9–4,7)	kW
Power Supply	Into Outdoor Unit	220 - 240 / 1 / 50	V / Ph / Hz
Power Input	Cooling / Heating	0,99 / 0,98	kW
Rated Power Input	Cooling / Heating	1,65	kW
Power Current	Cooling / Heating	4,4 / 4,4	A
Rated Power Current	Cooling / Heating	7,4	A
Pdesign	Cooling / Heating	3,5 / 3,2	kW
SEER / SCOP	-	7,2 / 4,1	W / W
Air Flow	Indoor Unit	680 / 620 / 560 / 490 / 450 / 420 / 390	m3 / h
Air Flow	Outdoor Unit	1950	m3 / h
Sound Pressure Level at 1 m	Indoor Unit	41 / 38 / 36 / 33 / 30 / 27 / 25 / 19	dB(A)
Sound Pressure Level at 1 m	Outdoor Unit	52	dB(A)
Sound Power Level	Indoor unit	60 / 52 / 50 / 47 / 44 / 41 / 39	dB(A)
Sound Power Level	Outdoor unit	63	dB(A)
Dehumidifying Volume	-	1,4	l / h
Refrigerant / Charge / Eq. CO2	-	R32 / 0,57 / 0,38	type / kg / t
Additional Refrigerant	-	16	g / m
Refrigerant Liquid Pipe	Diameter	01.04.2006	inch / mm
Refrigerant Gas Pipe	Diameter	3/8 / 9,5	inch / mm
Max pipe length without additional refrigerant	-	5	m
Min. / Max. Pipe Length	-	Mrz 15	m
Max. Elevation	-	10	m
Dimension (w x h x d)	Indoor Unit	837 × 293 × 200	mm
Dimension (w x h x d)	Outdoor Unit	732 × 555 × 330	mm
Package (w x h x d)	Indoor Unit	896 × 373 × 272	mm
Package (w x h x d)	Outdoor Unit	794 × 376 × 615	mm
Net / Gross Weight	Indoor Unit	9,5 / 11,5	kg
Net / Gross Weight	Outdoor Unit	25,5 / 28,0	kg
Set Temperature range	-	16 ~ 30	°C
Operating Temperature Range	Cooling	-15 ~ 50	°C
Operating Temperature Range	Heating	- 25 ~ 30	°C