

Capacity	Cooling / Heating	5,3 (0,9–6,3) / 5,4 (1,1–7,0)	kW
Power Supply	Into Outdoor Unit	220 - 240 / 1 / 50	V / Ph / Hz
Power Input	Cooling / Heating	1,53 / 1,39	kW
Rated Power Input	Cooling / Heating	2,4	kW
Power Current	Cooling / Heating	7,2 / 6,3	A
Rated Power Current	Cooling / Heating	10,5	A
Pdesign	Cooling / Heating	5,3 / 4,2	kW
SEER / SCOP	-	7,3 / 4,2	W / W
Air Flow	Indoor Unit	1000 / 850 / 760 / 650 / 580 / 520 / 450	m ³ / h
Air Flow	Outdoor Unit	2200	m ³ / h
Sound Pressure Level at 1 m	Indoor Unit	45 / 42 / 40 / 37 / 34 / 29 / 26 / 23	dB(A)
Sound Pressure Level at 1 m	Outdoor Unit	56	dB(A)
Sound Power Level	Indoor unit	60 / 55 / 53 / 50 / 47 / 42 / 39	dB(A)
Sound Power Level	Outdoor unit	65	dB(A)
Dehumidifying Volume	-	1,9	l / h
Refrigerant / Charge / Eq. CO2	-	R32 / 0,85 / 0,57	type / kg / t
Additional Refrigerant	-	16	g / m
Refrigerant Liquid Pipe	Diameter	01.04.2006	inch / mm
Refrigerant Gas Pipe	Diameter	01.02.2012	inch / mm
Max pipe length without additional refrigerant	-	5	m
Min. / Max. Pipe Length	-	Mrz 25	m
Max. Elevation	-	10	m
Dimension (w x h x d)	Indoor Unit	993 × 311 × 222	mm
Dimension (w x h x d)	Outdoor Unit	802 × 555 × 350	mm
Package (w x h x d)	Indoor Unit	1055 × 385 × 298	mm
Package (w x h x d)	Outdoor Unit	872 × 398 × 620	mm
Net / Gross Weight	Indoor Unit	12,5 / 15,0	kg
Net / Gross Weight	Outdoor Unit	31,5 / 34,0	kg
Set Temperature range	-	16 ~ 30	°C
Operating Temperature Range	Cooling	-15 ~ 50	°C
Operating Temperature Range	Heating	- 25 ~ 30	°C