

Outdoor unit	RXM60B5V1B		
Indoor unit	FBA60A2VEB9		
Function			
Kühlung	Ja		
Heizen	Ja		
	Average (mandatory) Warmer (if designated) Colder (if designated)		
Element	Symbol	Wert	Gerät
Design Load			
Kühlung	Pdesignc	5.70	kW
heating / Average	Pdesignh	4.60	kW
heating / Warmer	Pdesignh	2.44	kW
heating / Colder	Pdesignh	2.13	kW
Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj			
Tj = 35°C	Pdc	5.70	kW
Tj = 30°C	Pdc	4.20	kW
Tj = 25°C	Pdc	2.71	kW
Tj = 20°C	Pdc	2.13	kW
Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	Pdh	4.09	kW
Tj = 2°C	Pdh	2.44	kW
Tj = 7°C	Pdh	1.60	kW
Tj = 12°C	Pdh	1.79	kW
Tj = Bivalent temperature	Pdh	4.09	kW
Tj = operating limit	Pdh	3.85	kW
Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj			
Tj = 35°C	EERd	3.48	-
Tj = 30°C	EERd	5.05	-
Tj = 25°C	EERd	7.97	-
Tj = 20°C	EERd	8.54	-
Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	COPd	3.01	-
Tj = 2°C	COPd	4.18	-
Tj = 7°C	COPd	4.41	-
Tj = 12°C	COPd	5.32	-
Tj = Bivalent temperature	COPd	3.01	-
Tj = operating limit	COPd	2.11	-
Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj			
Tj = 2°C	COPd	4.18	-
Tj = 7°C	COPd	4.41	-
Tj = 12°C	COPd	5.32	-
Tj = Bivalent temperature	COPd	4.18	-
Tj = operating limit	COPd	2.11	-
Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	COPd	-	-
Tj = 2°C	COPd	-	-
Tj = 7°C	COPd	-	-
Tj = 12°C	COPd	-	-
Tj = Bivalent temperature	COPd	-	-
Tj = operating limit	COPd	-	-
Tj = -15°C	COPd	-	-
Bivalent temperature			
heating / Average	Tbiv	-7	°C
heating / Warmer	Tbiv	2	°C
heating / Colder	Tbiv	0	°C
operating limit			
heating / Average	Tol	-15	°C
heating / Warmer	Tol	-15	°C
heating / Colder	Tol	0	°C
Cycling interval capacity			
for cooling	Pcyc		kW
for heating	Pcych		kW
Degradation co-efficient cooling**	Cdc	0.25	-
Cycling interval efficiency			
for cooling	EErCyc		-
for heating	COPcyc		-
Degradation co-efficient cooling**	Cdh	0.25	-
Electric power input in power models other than 'active mode'			
Off mode	Poff	0.013	kW
Standby mode	Psb	0.013	kW
Thermostat-off mode	PTO	0	kW
Crankcase heater mode	PCK	0	kW
Annual electricity consumption			
Kühlung	QCE	336	kWh/a
heating / Average	QHE	1,607	kWh/a
heating / Warmer	QHE	770	kWh/a
heating / Colder	QHE	0	kWh/a
Capacity control			
Fest	N		
Gestaffelt	N		
Variable	N		
Other items			
Sound power level (indoor/outdoor)	LWA	56.0 / 63.0	db(A)
Global warming potential	GWP	675.0	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	18.0 / 46.6	m ³ /min
Contact details for obtaining more information	Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium		

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.

** if default Cd = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating of cooling cycling test value is required.