

| | | | | | | | |
|---|----------------------|-------------|-------------------|--|---------------------|-------------|-----------------------|
| Outdoor unit | | RXM71R2V1B | | | | | |
| Indoor unit | | FTXM71R2V1B | | | | | |
| Function | | | | Heating season | | | |
| Kühlung | | Ja | | Average (mandatory) | | Ja | |
| Heizen | | Ja | | Warmer (if designated) | | Ja | |
| | | | | Colder (if designated) | | Nein | |
| Element | Symbol | Wert | Maßeinheit | Element | Symbol | Wert | Maßeinheit |
| Design Load | | | | Seasonal efficiency | | | |
| Kühlung | P _{designc} | 7.10 | kW | Kühlung | SEER | 6.20 | - |
| heating / Average | P _{designh} | 6.20 | kW | heating / Average | SCOP / A | 4.10 | - |
| heating / Warmer | P _{designh} | 3.34 | kW | heating / Warmer | SCOP / W | 5.74 | - |
| heating / Colder | P _{designh} | | kW | heating / Colder | SCOP / C | | - |
| Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj | | | | Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj | | | |
| Tj = 35 °C | P _{dc} | 7.10 | kW | Tj = 35 °C | EERd | 3.03 | - |
| Tj = 30 °C | P _{dc} | 5.24 | kW | Tj = 30 °C | EERd | 4.88 | - |
| Tj = 25 °C | P _{dc} | 3.37 | kW | Tj = 25 °C | EERd | 7.39 | - |
| Tj = 20 °C | P _{dc} | 2.60 | kW | Tj = 20 °C | EERd | 9.69 | - |
| Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = -7 °C | P _{dh} | 5.49 | kW | Tj = -7 °C | COPd | 2.14 | - |
| Tj = 2 °C | P _{dh} | 3.34 | kW | Tj = 2 °C | COPd | 4.18 | - |
| Tj = 7 °C | P _{dh} | 2.32 | kW | Tj = 7 °C | COPd | 5.80 | - |
| Tj = 12 °C | P _{dh} | 2.38 | kW | Tj = 12 °C | COPd | 7.17 | - |
| Tj = Bivalent temperature | P _{dh} | 5.49 | kW | Tj = Bivalent temperature | COPd | 2.14 | - |
| Tj = operating limit | P _{dh} | 4.23 | kW | Tj = operating limit | COPd | 1.75 | - |
| Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = 2 °C | P _{dh} | 3.34 | kW | Tj = 2 °C | COPd | 4.18 | - |
| Tj = 7 °C | P _{dh} | 2.32 | kW | Tj = 7 °C | COPd | 5.80 | - |
| Tj = 12 °C | P _{dh} | 2.38 | kW | Tj = 12 °C | COPd | 7.17 | - |
| Tj = Bivalent temperature | P _{dh} | 3.34 | kW | Tj = Bivalent temperature | COPd | 4.18 | - |
| Tj = operating limit | P _{dh} | 4.23 | kW | Tj = operating limit | COPd | 1.75 | - |
| Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj | | | | Declared coefficient of performance* / Colder season, at indoor temperature 20 °C and outdoor temperature Tj | | | |
| Tj = -7 °C | P _{dh} | | kW | Tj = -7 °C | COPd | | - |
| Tj = 2 °C | P _{dh} | | kW | Tj = 2 °C | COPd | | - |
| Tj = 7 °C | P _{dh} | | kW | Tj = 7 °C | COPd | | - |
| Tj = 12 °C | P _{dh} | | kW | Tj = 12 °C | COPd | | - |
| Tj = Bivalent temperature | P _{dh} | | kW | Tj = Bivalent temperature | COPd | | - |
| Tj = operating limit | P _{dh} | | kW | Tj = operating limit | COPd | | - |
| Tj = -15 °C | P _{dh} | | kW | Tj = -15 °C | COPd | | - |
| Bivalent temperature | | | | operating limit | | | |
| heating / Average | T _{biv} | -7 | °C | heating / Average | T _{ol} | -15 | °C |
| heating / Warmer | T _{biv} | 2 | °C | heating / Warmer | T _{ol} | -15 | °C |
| heating / Colder | T _{biv} | | °C | heating / Colder | T _{ol} | | °C |
| Cycling interval capacity | | | | Cycling interval efficiency | | | |
| for cooling | P _{cycc} | | kW | for cooling | EER _{cycc} | | - |
| for heating | P _{cych} | | kW | for heating | COP _{cycc} | | - |
| Degradation co-efficient cooling** | C _{dc} | 0.25 | - | Degradation co-efficient cooling** | C _{dh} | 0.25 | - |
| Electric power input in power models other than 'active mode' | | | | Annual electricity consumption | | | |
| Off mode | P _{off} | 0.001 | kW | Kühlung | Q _{CE} | 401 | kWh/a |
| Standby mode | P _{sb} | 0.001 | kW | heating / Average | Q _{HE} | 2,117 | kWh/a |
| Thermostat-off mode | P _{TO} | 0 | kW | heating / Warmer | Q _{HE} | 814 | kWh/a |
| Crankcase heater mode | P _{CK} | 0 | kW | heating / Colder | Q _{HE} | | kWh/a |
| Capacity control | | | | Other items | | | |
| Fest | N | | | Sound power level (indoor/outdoor) | L _{WA} | 60.0 / 66.0 | db(A) |
| Gestaffelt | N | | | Global warming potential | GWP | 675.0 | kgCO ₂ eq. |
| Variable | N | | | Rated air flow (indoor/outdoor) | - | 16.9 | m ³ /min |
| Contact details for obtaining more information | | | | Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium | | | |

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.

** if default C_d = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating or cooling cycling test value is required.