

Outdoor unit		RZAG71NZV1B	
Indoor unit		FCAHG71HVEB	
Function		Heating season	
Kühlung	Ja	Average (mandatory)	Ja
Heizen	Ja	Warmer (if designated)	Nein
		Colder (if designated)	Nein
Element	Symbol	Wert	Gerät
Design Load			
Kühlung	P _{designc}	6.80	kW
heating / Average	P _{designh}	4.70	kW
heating / Warmer	P _{designh}		kW
heating / Colder	P _{designh}		kW
Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur T _j			
T _j = 35 °C	P _{dc}	6.80	kW
T _j = 30 °C	P _{dc}	5.01	kW
T _j = 25 °C	P _{dc}	3.22	kW
T _i = 20 °C	P _{dc}	2.64	kW
Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur T _j			
T _j = 35 °C	EER _d	4.13	-
T _j = 30 °C	EER _d	5.96	-
T _j = 25 °C	EER _d	10.19	-
T _i = 20 °C	EER _d	14.60	-
Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	P _{dh}	4.16	kW
T _j = 2 °C	P _{dh}	2.53	kW
T _j = 7 °C	P _{dh}	1.79	kW
T _j = 12 °C	P _{dh}	2.01	kW
T _j = Bivalent temperature	P _{dh}	4.70	kW
T _i = operating limit	P _{dh}	4.70	kW
Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	COP _d	3.32	-
T _j = 2 °C	COP _d	4.57	-
T _j = 7 °C	COP _d	5.48	-
T _j = 12 °C	COP _d	7.02	-
T _j = Bivalent temperature	COP _d	2.97	-
T _i = operating limit	COP _d	2.97	-
Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature T _j			
T _j = 2 °C	P _{dh}		kW
T _j = 7 °C	P _{dh}		kW
T _j = 12 °C	P _{dh}		kW
T _j = Bivalent temperature	P _{dh}		kW
T _i = operating limit	P _{dh}		kW
Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature T _j			
T _j = 2 °C	COP _d		-
T _j = 7 °C	COP _d		-
T _j = 12 °C	COP _d		-
T _j = Bivalent temperature	COP _d		-
T _i = operating limit	COP _d		-
Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	P _{dh}		kW
T _j = 2 °C	P _{dh}		kW
T _j = 7 °C	P _{dh}		kW
T _j = 12 °C	P _{dh}		kW
T _j = Bivalent temperature	P _{dh}		kW
T _j = operating limit	P _{dh}		kW
T _i = -15 °C	P _{dh}		kW
Bivalent temperature			
heating / Average	T _{biv}	-10	°C
heating / Warmer	T _{biv}		°C
heating / Colder	T _{biv}		°C
Cycling interval capacity			
for cooling	P _{cycc}		kW
for heating	P _{cych}		kW
Degradation co-efficient cooling**	C _{dc}	0.25	-
Cycling interval efficiency			
for cooling	EER _{cycc}		-
for heating	COP _{cycc}		-
Degradation co-efficient cooling**	C _{dh}	0.25	-
Electric power input in power models other than 'active mode'			
Off mode	P _{off}	0.009	kW
Standby mode	P _{sb}	0.009	kW
Thermostat-off mode	P _{TO}	0.013	kW
Crankcase heater mode	P _{CK}	0	kW
Annual electricity consumption			
Kühlung	Q _{CE}	301	kWh/a
heating / Average	Q _{HE}	1,427	kWh/a
heating / Warmer	Q _{HE}		kWh/a
heating / Colder	Q _{HE}		kWh/a
Capacity control			
Fest	N		
Gestaffelt	N		
Variable	N		
Other items			
Sound power level (indoor/outdoor)	L _{WA}	53.0 / 64.0	db(A)
Global warming potential	GWP	675	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	23.6 / 68	m ³ /min
Contact details for obtaining more information		Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium	

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.

** if default C_d = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating or cooling cycling test value is required.