

PRODUCT INFORMATION (*1)

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-EF25VGW / MSZ-EF25VGS / MSZ-EF25VGB
	OUTDOOR MODEL	MSZ-EF25VGKW / MSZ-EF25VGKS / MSZ-EF25VGBK MUZ-EF25VG

Function (indicate if present)	
cooling	Y
heating	Y

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	N

Item	symbol	value	unit
Design load			
cooling	P _{designc}	2.5	kW
heating/Average	P _{designh}	2.4	kW
heating/Warmer	P _{designh}	1.3	kW
heating/Colder	P _{designh}	x	kW

Item	symbol	value	unit
Seasonal efficiency			
cooling	SEER	9.1	-
heating/Average	SCOP/A	4.7	-
heating/Warmer	SCOP/W	5.8	-
heating/Colder	SCOP/C	x	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature T_j			
T _j =35°C	P _{dc}	2.5	kW
T _j =30°C	P _{dc}	1.9	kW
T _j =25°C	P _{dc}	1.2	kW
T _j =20°C	P _{dc}	0.8	kW

Declared energy efficiency ratio, at indoor temperature 27(19) °C and outdoor temperature T_j			
T _j =35°C	EERd	4.7	-
T _j =30°C	EERd	7.6	-
T _j =25°C	EERd	10.5	-
T _j =20°C	EERd	15.2	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature T_j			
T _j =-7°C	P _{dh}	2.2	kW
T _j =2°C	P _{dh}	1.3	kW
T _j =7°C	P _{dh}	0.8	kW
T _j =12°C	P _{dh}	0.6	kW
T _j =bivalent temperature	P _{dh}	2.4	kW
T _j =operating limit	P _{dh}	2.0	kW

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature T_j			
T _j =-7°C	COPd	2.8	-
T _j =2°C	COPd	4.8	-
T _j =7°C	COPd	6.2	-
T _j =12°C	COPd	6.7	-
T _j =bivalent temperature	COPd	2.5	-
T _j =operating limit	COPd	2.2	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature T_j			
T _j =2°C	P _{dh}	1.3	kW
T _j =7°C	P _{dh}	0.8	kW
T _j =12°C	P _{dh}	0.6	kW
T _j =bivalent temperature	P _{dh}	1.3	kW
T _j =operating limit	P _{dh}	2.0	kW

Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature T_j			
T _j =2°C	COPd	4.8	-
T _j =7°C	COPd	6.2	-
T _j =12°C	COPd	6.7	-
T _j =bivalent temperature	COPd	4.8	-
T _j =operating limit	COPd	2.2	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature T_j			
T _j =-7°C	P _{dh}	x	kW
T _j =2°C	P _{dh}	x	kW
T _j =7°C	P _{dh}	x	kW
T _j =12°C	P _{dh}	x	kW
T _j =bivalent temperature	P _{dh}	x	kW
T _j =operating limit	P _{dh}	x	kW
T _j =-15°C	P _{dh}	x	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature T_j			
T _j =-7°C	COPd	x	-
T _j =2°C	COPd	x	-
T _j =7°C	COPd	x	-
T _j =12°C	COPd	x	-
T _j =bivalent temperature	COPd	x	-
T _j =operating limit	COPd	x	-
T _j =-15°C	COPd	x	-

Bivalent temperature			
heating/Average	T _{biv}	-10	°C
heating/Warmer	T _{biv}	2	°C
heating/Colder	T _{biv}	x	°C

Operating limit temperature			
heating/Average	T _{ol}	-15	°C
heating/Warmer	T _{ol}	-15	°C
heating/Colder	T _{ol}	x	°C

Cycling interval capacity			
for cooling	P _{cycc}	x	kW
for heating	P _{cyh}	x	kW
Degradation co-efficient cooling	C _{dc}	0.25	-

Cycling interval efficiency			
for cooling	EER _{cycc}	x	-
for heating	COP _{cyh}	x	-
Degradation co-efficient heating	C _{dh}	0.25	-

Electric power input in power modes other than 'active mode'			
off mode	P _{OFF}	1.0	W
standby mode	P _{SB}	1.0	W
thermostat - off mode	P _{TO}	8.0	W
crankcase heater mode	P _{CK}	0.0	W

Annual electricity consumption			
cooling	Q _{CE}	96	kWh/a
heating/Average	Q _{HE}	713	kWh/a
heating/Warmer	Q _{HE}	311	kWh/a
heating/Colder	Q _{HE}	x	kWh/a

Capacity control (indicate one of three options)	
fixed	N
staged	N
variable	Y

Other items			
Sound power level (indoor/outdoor)	L _{WA}	60/58	dB(A)
Global warming potential	GWP (*2)	675	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	630/1668	m ³ /h

Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@MitsubishiElectric.co.jp
--	---

(*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No. 206/2012.
 (*2) This GWP value is based on Regulation(EU)No. 517/2014 from IPCC 4th Assessment Report.
 For Regulation (EU) No. 626/2001, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.

TECHNICAL DOCUMENTATION (¹)

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-EF25VGW / MSZ-EF25VGS / MSZ-EF25VGB	299H*885W*195D (mm)
	OUTDOOR MODEL	MSZ-EF25VGKW / MSZ-EF25VGKS / MSZ-EF25VGKB MUZ-EF25VG	550H*800W*285D (mm)

Function	
cooling	Y
heating	Y


The heating season	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	N

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
Seasonal efficiency (²)			
cooling	SEER	9.1	-
heating/Average	SCOP/A	4.7	-
heating/Warmer	SCOP/W	5.8	-
heating/Colder	SCOP/C	x	-

Energy efficiency class			
cooling	SEER	A+++	-
heating/Average	SCOP/A	A++	-
heating/Warmer	SCOP/W	A+++	-
heating/Colder	SCOP/C	x	-

Other items			
Sound power level (indoor/outdoor)	L _{WA}	60/58	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP (³)	675	kgCO ₂ eq.

identification and signature of the person empowered to bind the supplier	
	Tadashi Saito Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS(THAILAND) CO.,LTD

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No. 626/2011.
 (2) SEER/SCOP values are measured based on EN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.
 (3) This GWP value is based on Regulation(EU)No. 517/2014 from IPCC 4th Assessment Report.
 For Regulation (EU) No. 626/2001, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.