

Indoor unit model name FDT50VH Outdoor unit model name SRC50ZSX-W2

Refrigerant	R32	GWP	6	75	
contribute less to appliance contair would be leaked over a period of	global warming than ns a refrigerant fluid to the atmosphere, t	n a refrigerant with a GWP e he impact on to interfere wi	with hig qual to global v	gher GWP, if leak 675. This means varming would be	obal warming potential (GWP) would sed to the atmosphere. This that if 1kg of this refrigerant fluid e 675 times higher than 1kg of CO2, yourself or disassemble the product
Cooling mode					
SEER		8.0			
Energy efficie		A++			
Design load (I Energy consu		5.0		oor voor boso	h on standard test results
					d on standard test results. used and where it is located.
Heating mode (A	verage)				
SCOP		4.7			
Energy efficie		A++			
Design load (I			kW	<b>`</b>	
Declared capa		4.0		(-10°C)	
Back up heati			kW	(-10°C)	
Energy consu					d on standard test results.
Actual energ	gy consumption will	i depend on	now tr	le appliance is l	used and where it is located.
Heating mode (V	Varmer) Optional				
SCOP		-			
Energy efficie		-			
Design load (I			kW	(2°C)	
Declared capa			kW	(2°C)	
Back up heati			kW	(2°C)	h on standard test results
Energy consumption, - kWh per year.based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.					
	gy concumption wi		now a		
Heating mode (C	older) Optional				
SCOP		-			
Energy efficie		-			
Design load (I			kW	(-22°C)	
Declared capa			kW	(-22°C)	
Back up heati	8 . ,		kW	(-22°C)	
Energy consu					d on standard test results.
Actual energy consumption will depend on how the appliance is used and where it is located.					
Sound power	level (indoor)	55		dB(A)	
	level (outdoor)	63		dB(A)	