

| | | |
|--|------------------------|---|
| Models | Indoor unit: | HSB60 |
| | Outdoor unit: | FDCW60VNX-A |
| | Tank: | - |
| Heat pump type: | Air-to-water heat pump | Equipped with a supplementary heater: [[yes]/no] |
| Low-temperature heat pump: | [yes/[no]] | Heat pump combination heater: [yes/[no]] |
| Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application | | |
| Declared climate condition: | Average | |

| Item | Symbol | Value | Unit | Item | Symbol | Value | Unit |
|--|--|-------|------|---|-------------------------|-------|-------------------|
| Rated heat output(*) | <i>P_{rated}</i> | 5.3 | kW | Seasonal space heating energy efficiency | η_s | 138 | % |
| Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature T _j | | | | Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature T _j | | | |
| T _j = -7°C | <i>P_{dh}</i> | 4.7 | kW | T _j = -7°C | <i>COP_d</i> | 1.88 | - |
| T _j = +2°C | <i>P_{dh}</i> | 2.8 | kW | T _j = +2°C | <i>COP_d</i> | 3.59 | - |
| T _j = +7°C | <i>P_{dh}</i> | 1.8 | kW | T _j = +7°C | <i>COP_d</i> | 4.72 | - |
| T _j = +12°C | <i>P_{dh}</i> | 2.7 | kW | T _j = +12°C | <i>COP_d</i> | 6.47 | - |
| T _j = bivalent temperature | <i>P_{dh}</i> | 4.7 | kW | T _j = bivalent temperature | <i>COP_d</i> | 1.88 | - |
| T _j = operation limit temperature | <i>P_{dh}</i> | 4.1 | kW | T _j = operation limit temperature | <i>COP_d</i> | 1.77 | - |
| For air-to-water heat pumps: T _j = -15°C (if TOL < -20°C) | <i>P_{dh}</i> | - | kW | For air-to-water heat pumps: T _j = -15°C (if TOL < -20°C) | <i>COP_d</i> | - | - |
| Bivalent temperature | <i>T_{biv}</i> | -7 | °C | For air-to-water heat pumps: Operation limit temperature | <i>TOL</i> | -10 | °C |
| Cycling interval capacity for heating | <i>P_{cych}</i> | - | kW | Cycling interval efficiency | <i>COP_{cy}</i> | - | - |
| Degradation co-efficient(**) | <i>C_{dh}</i> | 0.99 | - | Heating water operating limit temperature | <i>WTOL</i> | 58 | °C |
| Power consumption in modes other than active mode | | | | Supplementary heater | | | |
| Off mode | <i>P_{OFF}</i> | 0.007 | kW | Rated heat output(*) | <i>P_{sup}</i> | 1.2 | kW |
| Thermostat-off mode | <i>P_{TO}</i> | 0.012 | kW | Type of energy input | Electricity | | |
| Standby mode | <i>P_{SB}</i> | 0.012 | kW | | | | |
| Crankcase heater mode | <i>P_{CK}</i> | 0.000 | kW | | | | |
| Other items | | | | | | | |
| Capacity control | variable | | | Sound power level, outdoors | <i>L_{WA}</i> | 53 | dB |
| Sound power level, indoors | <i>L_{WA}</i> | 33 | dB | For air-to-water heat pumps: Rated air flow rate, outdoors | | 2526 | m ³ /h |
| For heat pump combination heater | | | | | | | |
| Declared load profile | - | | | Daily electricity consumption | <i>Q_{elec}</i> | - | kWh |
| Water heating energy efficiency | η_{wh} | - | % | Annual electricity consumption | <i>AEC</i> | - | kWh |
| Contact details | MHIAE SERVICES B.V. (Wholly-owned subsidiary of MITSUBISHI HEAVY INDUSTRIES AIR-CONDITIONING EUROPE, LTD.) Herikerbergweg 238, Luna Arena, 1101 CM Amsterdam, Netherlands . P.O.Box 23393 1100 DW Amsterdam, Netherlands | | | | | | |
| (*) For heat pump space heaters and heat pump combination heaters, the rated heat output <i>P_{rated}</i> is equal to the design load for heating <i>P_{designh}</i> , and the rated heat output of a supplementary heater <i>P_{sup}</i> is equal to the supplementary capacity for heating <i>sup(T_j)</i> . | | | | | | | |
| (**) If <i>C_{dh}</i> is not determined by measurement then the default degradation coefficient is <i>C_{dh} = 0,9</i> . | | | | | | | |